

SAFETY WARNING!

Always use the correct tools, and wear safety goggles. We STRONGLY recommend installation by a licensed mechanic on a properly secured locking lift.

TIRE FITMENT ADVICE.

The best way to ensure proper tire fitment is to install the kit before purchasing your wheels and tires. Always test fit tires and wheels before purchasing.

VEHICLE RIDE WARNING!

Trucks with lift or level kits installed have a higher center of gravity. Aggressive and sudden direction changes may cause a tip over.

Installation Tips.

Always use caution handling ABS or wheel sensor wiring. Avoid tension of any kind on wiring harness as this may cause damage or failure.

- 1. Trucks are often not level side to side from the factory. Please measure before installation and note the measurements below.
- 2. Re-torque all hardware to manufacturers specifications.
- 3. When aligning, to get the best tire wear use our supplied specifications. OEM specifications are for trucks with stock wheels and tires. Larger tires will wear differently.
- 4. All instructions are written with vehicle on a 2-post lift with tires removed.

Alignment Notes.


We recommend that a technician with experience doing alignments on lifted trucks perform the alignment. Large tires wear differently than OEM sized tires. Always do an alignment after changing tires on a vehicle.

Ride Height Chart

Driver Front:	Driver Rear:	Pass. Front:	Pass. Rear:
Stock height	Stock height	Stock height	Stock height
Lifted height	Lifted height	Lifted height	Lifted height

Installation Instructions - Kit # 905096 - Toyota 4Runner/FJ Cruiser Rear Lift Kit







Push bolt in and all the way through the bumpstop. You may need to use a screwdriver or similar to achieve this.



Bolt should extend out of top of bumpstop.



Take Traxda Spacer and install onto bumpstop, pushing bolt through hole.



Tighten nut onto bolt, attaching Traxda Spacer to bumpstop.



The completed installation.